



# TWINGLE BASIC

## SYSTEMS

TWINGLE SERIES – Six white light colours, three modules, one concept: directed, additive light with a low luminance emphasises goods and architectural elements without dazzling the observer. In that way you create a pleasant sales atmosphere with elegant and high-class effects. TWINGLE BASIC generates homogeneous ambient lighting in the room.



### Ideal applications

Excellent lighting architecture for modern store concepts



### Lighting - rethought

Additive, directed light with a low luminance



### Systemic product family

Modules for accent and basic lighting as well as for vertical lighting



### Variety in design





Modules in white, black and bi-colour





# TWINGLE BASIC

# oktalite

[www.oktalite.com/twingle-basic-s](http://www.oktalite.com/twingle-basic-s)

Type of luminaire	Systems
Application areas	Wide-area merchandise illumination
Pan/tilt range	fixed
Mounting	3-circuit power track adapter, not suitable for vertical mounting
Lighting technology	LED <sup>IQ</sup>
Lumen category	2000 lm - 3000 lm
Light colour White	2700 K, 3000 K, 3100 K Best Colour, 3100 K Efficient Colour, 3500 K, 4000 K
Cooling	passive
Supply unit	DALI driver integrated
Luminaire colour	Bicolour finish RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	DALI
Weight	Approx. 1.9 kg
Components	 Luminaire housing
Test seal	  



Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T +49 221 59767-0 · F +49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2019-06-25

**TWINGLE BASIC****oktalite**

Lumen category	Light colour	CRI R <sub>a</sub>	system luminous flux	System performance	Order number		
					white	bicolour	black
2000 lm	3100 K Best Colour	95	1805 lm	28 W	10164576	10164577	10164578
3000 lm	2700 K	82	2155 lm	28 W	10164567	10164568	10164569
3000 lm	3000 K	82	2215 lm	28 W	10164570	10164571	10164572
3000 lm	3100 K Efficient Colour	82	2180 lm	28 W	10164573	10164574	10164575
3000 lm	3500 K	82	2265 lm	28 W	10164579	10164580	10164581
3000 lm	4000 K	84	2320 lm	28 W	10164582	10164583	10164584



Beam angle	Reflector colour	LO
------------	------------------	----

wide

silver

61 %

Twingle Basic			
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) E(C90) [lx/klm]
1	84 143	578	227 158
2	168 285	145	57 39
3	252 428	64	25 18

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T +49 221 59767-0 · F +49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2019-06-25