



AGIRA PLUS

RECESSED LUMINAIRES

As a high-performance recessed directional LED spotlight, AGIRA PLUS rounds off the portfolio – in that way concepts with different ceiling heights and area sizes can be easily implemented with one luminaire type. The spotlights can be turned through 355° and tilted in two directions through 30° in each case – which is ideal for targeted and flexible illumination of goods. AGIRA PLUS combines the advantages of a gimbal-mounted luminaire with those of a classic recessed spotlight. Optionally fitted with Tunable White module. This makes the precise adjustment of the light possible as regards intensity and colour temperature.



Ideal application range

Optimum use in the case of great ceiling heights



Uncluttered ceiling pattern and high flexibility

Turning through 355°, tilting in both directions through 30°, makes optimum luminaire alignment and light directing possible.



Extensive variety

Our white light colours and special light colours for the fresh area are available for selection




Practical installation

Tool-free installation thanks to simple spring mechanism




Intelligent light

Smart lighting management optionally with control line or wireless




FOOD



FASHION



SHOP



AUTOMOTIVE

AGIRA PLUS

www.oktalite.com/agira-plus

Luminaire type	Recessed luminaires
Application areas	Base illumination, accent lighting
Range of action	Can be rotated through 355° and swiveled through 90
Fastening	Spring fastening (angle fastening)
Ceiling thickness	1-25 mm
Ceiling cut-out	175 mm
Lighting technology	LED, LED IQ DALI, LED IQ BLE
Beam angel	Spot, Medium Flood, Flood, Wide Flood, Very Wide Flood
LED luminous flux class	1500 lm - 7000 lm
Light colour CRI 80	2700 K, 3000 K, 3500 K, 4000 K
Light colour CRI 90	3100 K - Brilliant Colour, 3200 K - Efficient White, 4000 K - Efficient Cool
Light colour Food	2700 K - Brilliant Food, Meat, Meat + Fish
Variable light colour	Tunable Meat, Tunable White (2700 K - 6500 K)
Supply unit	Integrated driver
	RAL 9005 jet black
Luminaire colour	RAL 9006 white aluminum RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Weight	approx. 1.3 kg
Test mark	