



TOKO

RECESSED LUMINAIRES

Particularly in the fashion area, an ingenious mixture of coherent basic lighting and well-balanced accentuation is required. Here TOKO is just right, since this LED downlight performs both tasks with virtuosity. It is small and unobtrusive in its design. Its fresh light illuminates the room homogeneously as far as the very last corner. Thanks to the 3D faceted reflector and four beam angles, accents can also be systematically set with TOKO.



Four beam angles thanks to 3D faceted reflector
Homogeneous or accentuated illumination is very easy: Beam angles of 28°, 38°, 48° und 60°



Small dimensions

Ceiling cut-out only 130 mm, recessing depth only 100 mm



Well thought-out attachment

Innovative mounting spring for ease of attachment





Large choice of LEDs

Six white light colours up to 4000 lm



Intelligent light

Smart lighting management optionally with control line or wireless



TOKO

www.oktalite.com/toko

Luminaire type	Recessed luminaires
Application areas	Base illumination
Range of action	fixed
Fastening	Spring fastening (angle fastening)
Ceiling thickness	1-25 mm
Ceiling cut-out	130 mm
Lighting technology	LED, LED IQ DALI, LED IQ BLE
Beam angel	Medium Flood, Flood, Wide Flood, Very Wide Flood
LED luminous flux class	2000 lm - 5000 lm
Light colour CRI 80	2700 K, 3000 K, 3500 K, 4000 K
Light colour CRI 90	3100 K – Brilliant Colour, 3200 K – Efficient White, 4000 K – Efficient Cool
Light colour Food	2700 K – Brilliant Food
Variable light colour	Active (2700 K – 6500 K)
Supply unit	Integrated driver
	RAL 9005 deep black
Luminaire colour	RAL 9006 white aluminum RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Weight	approx. 0,63 kg
Test mark	