# oktalite



# **CANILO**

Suspended luminaires

CANILO is characterized by a classic, elegant design and offers a special element to support the customer CI: The side flap can be customized in color. The recessed reflector with integrated glare ring offers a high level of visual comfort. The variable and tool-free adjustable suspension in the form of a current-carrying cable gives it an elegant look.



#### Individual style

Side flap can be color-matched to customer CI



## **Uniform effect**

The suspension and bracket specify the mounting direction and ensure a calm overall appearance if there are several luminaires.



### Various mounting options

A ceiling canopy, a ceiling round or an adapter for attaching to conductor rails are available for mounting



#### High visual comfort

Recessed reflector ensures good glare control with no loss of light











# oktalite

## **CANILO**

#### www.oktalite.com/canilo

Suspended luminaires Luminaire type

Application areas Accent lighting

Range of action rigid

Fastening 3P conductor rail, structure, installation

Ceiling thickness 1 - 25 mm

Pendulum length 1500 mm, 3000 mm

Lighting technology LED, LED IQ DALI

Beam angel Spot, Medium Flood, Flood, Wide Flood, Very Wide Flood

LED luminous flux class 2000 lm - 3000 lm

Light colour CRI 80 2700 K, 3000 K, 3500 K

3100 K - Brilliant Color, Light colour CRI 90

3200 K - Efficient White, 4000 K - Efficient Cool

Supply unit Integrated driver

RAL 9005 jet black

Luminaire colour RAL 9016 traffic white

Special colours on request

Surface structure powder-coated

Nominal voltage 220 - 240 V, 50/60Hz

Weight approx. 2.0

Test mark




Ø 150

Ø 105



1500

100



3000

100

Ø 105





